



DURAFIL

AUTO TECHNOLOGIES INC.

Part No.: R-121
R-122
R-123
Low VOC Compliant

PDS Form:
R121.122.123/LVCD AUS/0216_V01

FAST-FIL/MEDIUM-FIL/SLOW-FIL R-121/R-122/R-123

FAST, MEDIUM, SLOW REDUCERS



FAST-FIL R-121 / MEDIUM-FIL R-122 / SLOW-FIL R-123 are Low VOC, 250 g/L or less, Reducers designed to be used in all solvent based I/K urethane primers, urethane, acrylic enamel, and air dry enamel paint systems, basecoat paints, and clearcoats. These **Reducers** will provide you with the optimal spray viscosity, and flow properties necessary to extract the optimal performance from any solvent based system. You have a choice of three speeds of dry **Reducers** from Fast to Slow dry **R-121/R-122/R-123** to meet your speed of dry requirements. Select the appropriate speed of dry **Reducer** according to temperature and size of the repair surface to extract the optimum performance from any two component, Low VOC solventborne system.

Mix Ratio: As Recommended



Refer to Product Data Sheet
(PDS) R-121/R-122/R-123
for more information

Part No.	Description	Size	Units/ Case
R-121	FAST-FIL Fast Reducer	3.78 L/1 US Gallon	2
R-121.5	FAST-FIL Fast Reducer	18.9 L/5 US Gallons	Ea.
R-122	MEDIUM-FIL Medium Reducer	3.78 L/1 US Gallon	2
R-122.5	MEDIUM-FIL Medium Reducer	18.9 L/5 US Gallons	Ea.
R-123	SLOW-FIL Slow Reducer	3.78 L/1 US Gallon	2
R-123.5	SLOW-FIL Slow Reducer	18.9 L/5 US Gallons	Ea.

FEATURES

- Low V.O.C.
- Compatible With Most Solvent
Basecoat/Clearcoat Systems
- Compatible With Most Solvent
Primers & Topcoats Systems
- Offered in 3 Speeds of Dry



FAST-FIL / MEDIUM-FIL / SLOW-FIL

R-121 / R-122 / R-123

FAST, MEDIUM, & SLOW REDUCERS

FAST-FIL R-121 / MEDIUM-FIL R-122 / SLOW-FIL R-123 are Low VOC, 250 g/L or less, **Reducers** formulated to be used in all solvent based I/K urethane primers, urethane, acrylic enamel, and air dry enamel paint systems, basecoat paints, and clearcoats. These **Reducers** will provide you with the optimal spray viscosity, and flow properties necessary to extract the optimal performance from any solvent based system. You have a choice of three speeds of dry **Reducers** from Fast to Slow dry **R-121/R-122/R-123** to meet your speed of dry requirements. Select the appropriate speed of dry **Reducer** according to temperature and size of the repair surface to extract the optimum performance from any two component, Low VOC solventborne system.

PACKAGING:

3.78 L / 1 US GALLON PER CAN 4 CANS PER CASE
18.9 L / 5 US GALLONS PER PAIL

MATERIALS:


REDUCER	
R-121/R-121.5	FAST-FIL FAST REDUCER or
R-122/R-122.5	MEDIUM-FIL MEDIUM REDUCER or
R-123/R-123.5	SLOW-FIL SLOW REDUCER

PROTECTION:



Use only in a well ventilated area. Always wear the appropriate safety equipment. Consult with safety equipment supplier to ensure the proper safety equipment protective clothing are being used.

MIX RATIO:



Follow the manufacturers' directions.

PRODUCT DATA SHEET

PART NUMBER: R-121

R-122

R-123

Low VOC Compliant



PDS Form:


R121.122.123/LVCD AUS/0216_V01

SPRAY PRESSURE:



Follow the manufacturers' directions.

FLASH AND DRY TIME:



SAFETY & HANDLING:

Important: For Industrial Use Only by trained professionals using proper safety equipment. Prior to using be sure to read and understand the warnings of this product and all products it may require, since the mixture will have the hazards of all its components. Observe all precautions for all components. Use only with adequate ventilation and wear the appropriate safety equipment. Refer to Material Safety Data Sheet (MSDS) for more and current information regarding this product and handling instructions.

The data contained in this publication are based on our current knowledge and experience. Many factors may affect processing, application, and performance of our products. The data and information contained herein does not imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. We shall not accept any liability for damages, skill of user, personal protective clothing and equipment, the materials used and processing conditions. The sellers and manufacturers liability on any claim, including negligence, loss, damage or injury, direct or other-wise resulting from manufacture, sale, resale, delivery, repair or use of any goods covered by or furnished shall not exceed the cost of replacing product. Any descriptions, data, proportions, weights, etc. given herein are for general information purposes only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. The latest version can be obtained from our website at www.durafil.ca or by contacting your sales representative or us directly.



SOME OF OUR PRODUCTS...

FILLERS



PUTTIES



CLEAR COATS



PAINTS



Transparent Urethane Sealer



Plastic Adhesion Promoter



Reducers



Epoxy Primer



1K Urethane Primer



Silicone & Wax Remover



DURAFIL
AUTO TECHNOLOGIES INC.

1360 Blundell Road
Mississauga, ON L4Y 1M5 Canada
Telephone: 905.896.7171 Toll Free: 877.505.7171