



## CLEAN-FIL CF-125

### SILICONE & WAX REMOVER



**CLEAN-FIL CF-125** is a Low VOC Silicone & Wax Remover formulated to quickly and easily remove silicones, oil, waxes, grease, overspray, adhesives, engine oil, fingerprints, and other contaminants from surfaces to be refinished. **CF-125** can be applied to metal, undercoats, plastics, fiberglass, and cured or dried automotive painted finishes. **CF-125** is packaged ready-to-use and has been designed to be used before sanding, taping, priming, and sealing and should also be applied to the repair surface as a final wash prior to applying a topcoat.

**Mix Ratio:** None, Ready To Use

Part No.	Description	Size	Units/Case
CF-125	CLEAN-FIL Silicone & Wax Remover	3.78 L / 1 US Gallon	4
CF-125.5	CLEAN-FIL Silicone & Wax Remover	18.9 L / 5 US Gallons	Ea.



Refer to Product Data Sheet (PDS)  
CF-125 for more information

### FEATURES

- Low V.O.C.
- Excellent Cleaning Properties
- Leaves No Residue Behind
- No Streaking
- Easy To Apply
- Ready-To-Use
- Premium Ingredients



## CLEAN-FIL CF-125

### SILICONE & WAX REMOVER

---

**CLEAN-FIL CF-125 Silicone & Wax Remover** is a Low VOC cleaner formulated to easily and quickly remove silicone, wax, oil, grease, and other residue and contaminants from surfaces to be refinished. **CF-125** can be applied to metal, painted, primed, plastic, and fiberglass surfaces. **CF-125** is designed to be used before and after sanding, to clean and remove residue from the surface to be refinished. **CF-125** must also be applied to clean the repair surface again before applying any ground or top coat, such as primer, paint, or sealer to remove any residue from surface .

---

**PACKAGING:**                      **3.78 L / 1 US GALLON PER CAN      4 CANS PER CASE**  
   **18.9 L / 5 US GALLONS PER PAIL**

---

**APPROVED SUBSTRATES:** On metal, cured primed and painted surfaces, plastic and fiberglass surfaces.

---

#### SURFACE PREPARATION:




Apply a liberal amount of **CF-125** to a clean, lint free cloth/rag. Rubbing briskly, wipe off oil, wax, grease, and other contaminants from the surface. It is recommended that cloths/ rags be changed frequently to prevent the spreading of residue and other contaminants. Wipe dry surface immediately after applying **CF-125**. Do not let **CF-125** air dry on panel.

In case of hard to remove residue, repeat the entire application using new, clean cloths until the surface is completely clean.

---

#### MIX RATIO:



Ready To Use

**CF-125** is ready to use. No mixing required.

---



PDS Form:  
CF125/LVCD AUS/0518\_V02

### TECHNICAL INFORMATION:

<b>Appearance:</b>	Clear Liquid
<b>Weight Per Gallon:</b>	2.79 kg - 3.34 kg / 6.15 lbs - 7.36 lbs
<b>Specific Gravity:</b>	0.737 - 0.882
<b>% Solids by Weight:</b>	0 - 1
<b>Coats To Apply:</b>	1 - 2
<b>Pot Life:</b>	Not Applicable
<b>Mix Ratio:</b>	Ready To Use

### SAFETY & HANDLING:

**Important: For Industrial Use Only** by trained professionals using proper safety equipment. Prior to using be sure to read and understand the warnings of this product and all products it may require, since the mixture will have the hazards of all its components. Observe all precautions for all components. Use only with adequate ventilation and wear the appropriate safety equipment. Refer to Material Safety Data Sheet (MSDS) for more and current information regarding this product and handling instructions.

The data contained in this publication are based on our current knowledge and experience. Many factors may affect processing, application, and performance of our products. The data and information contained herein does not imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. We shall not accept any liability for damages, skill of user, personal protective clothing and equipment, the materials used and processing conditions. The sellers and manufacturers liability on any claim, including negligence, loss, damage or injury, direct or other-wise resulting from manufacture, sale, resale, delivery, repair or use of any goods covered by or furnished shall not exceed the cost of replacing product. Any descriptions, data, proportions, weights, etc. given herein are for general information purposes only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. The latest version can be obtained from our website at [www.durafil.ca](http://www.durafil.ca) or by contacting your sales representative or us directly.

